



Your Reliable Working Partner On Tough Terrains

The TF125, powered by a tough and reliable power-reed-valve air-cooled 2-stroke engine, is a bike that's tailor-equipped to fully meet the requirements of a run-about vehicle in versatile tough-work use. It topped off by special protectors, extended fenders, both right-and-left sidestands, big luggage carrier and wide-tread block pattern tires ready for rough road riding.

TF125



Solid Special White No.2 (30H)



Heavy-duty headlight protector



Large flat rear carrier and storage box



Functional engine guard bar and plate

- 123cm³, piston-reed-valve 2-stroke, air-cooled engine produces abundant usable torque with excellent fuel economy.
- Maintenance-free electronic ignition system delivers precise ignition at every engine rpm range.
- Cylinder and Crank Injection System (CCIS) assures necessary engine lubrication.
- 6-speed transmission with proper gear ratios chosen for smooth riding. Quick-action rack-and-pinion clutch design ensures light and positive clutch operation.
- Long-travel front and rear suspensions with smooth action. Rear shock absorbers come with 5-way spring preload adjustment.
- Large 13-liter fuel tank.
- Thick well-padded seat for rider's comfort.
- Wide-tread block pattern tires surely transfer engine power into traction.
- Sturdy steel protectors for brake and clutch levers.
- Useful clutch and brake lever locks convenient for short stop during work.
- Heavy-duty headlight protector is also capable as carrier with spring clip for light loading.
- Guard bar and plate protect the bottom of the engine.

- Extended front and rear mud flaps help protecting rider and motorcycle from mud and dirt.
- Large chain guard has advantage against dirt.
- Side stands, installed on both right and left sides for easy parking on uneven terrain.
- Large flat rear carrier.
- Convenient sturdy box underneath rear carrier for storing tools and other small items.

Specifications

Engine Type	2-stroke, 1-cylinder, air-cooled	
Engine Displacement	123 cm ³ (cc)	
Bore x Stroke	56.0 mm x 50.0 mm	
Compression Ratio	6.2 : 1	
Transmission	6-speed constant mesh	
Overall Length	2,170 mm (85.4 in.)	
Overall Width	935 mm (36.8 in.)	
Overall Height	1,150 mm (45.3 in.)	
Wheelbase	1,335 mm (52.6 in.)	
Ground Clearance	250 mm (9.8 in.)	
Seat Height	835 mm (32.9 in.)	
Curb Mass	102 kg (225 lbs.)	
Suspension	Front	Telescopic, coil spring, oil damped
	Rear	Swingarm type, coil spring, oil damped
Brakes	Front	Drum
	Rear	Drum
Tires	Front	2.75-21 4PR, tube type
	Rear	4.10-18 4PR, tube type
Ignition Type	Electronic ignition (CDI)	
Fuel Tank Capacity	13.0 L (3.4 US gal.)	

Colors



Solid Special White No.2 (30H)

Specifications, appearances, colors (including body color), equipments, materials and other aspects of the "SUZUKI" products shown on this leaflet are subject to change by SUZUKI at any time without notice and they may vary depending on local conditions or requirements. Some models are not available in some territories. Each model may be discontinued without notice. Please inquire at your local dealer for details of any such changes.

■ Always wear a helmet, eye protection and protective clothing. ■ Enjoy riding safely.
■ Read your Owner's Manual carefully. ■ Never ride under the influence of alcohol or other drugs.

PRINTED IN JAPAN TF125 Leaflet 99999-A1307-151 SEP.'08
SUZUKI MOTOR CORPORATION
300 TAKATSUKA, MINAMI, HAMAMATSU, JAPAN

www.globalsuzuki.com

