



including ABS version "Bandit 1250SA"



Experience Refined Total Balance

Exciting quantity and quality of torque from its 1255cm³ liquid-cooled engine featuring advanced digital fuel injection. Distinctive styling and sporting comfort, enhanced with a sleek half-fairing and effective windscreen. Heavyweight power with unmatched quality and value. Experience the Bandit 1250S.



including ABS version "Bandit 1250SA"



Photo : Bandit 1250S

Metallic Alba Blue (YUF)

 1255cm³ liquid-cooled fuel-injected DOHC engine for extra-smooth acceleration and relaxed highway cruising.

Well-exposed, symmetrical-layout (center-cam-drive) powerplant forms the core of the Bandit's beautiful naked bike appearance.

Suzuki Dual Throttle Valve (SDTV) fuel injection brings better response feel, smoother power output, and reduced emissions.

 Long-wearing, tough Suzuki Composite Electrochemical Material (SCEM) cylinder-bore plating.

Secondary balancer shaft enhances the engine's smooth operation.

Liquid-cooled oil cooler helps keep the engine running cool.

6-speed transmission with gear ratios chosen for powerful acceleration and smooth highway cruising.
 Antilock Brake System (ABS)* monitors wheel speed, and

matches stopping power to available traction. (Bandit 1250SA only)

■ Classic tube-frame chassis, with rake and trail chosen for an excellent balance between sporty handing and highway cruising comfort.

43mm-stanchion-tube front forks and single rear shock absorber, both are spring-preload-adjustable. ■ Fully floating 310mm-disc dual front brakes with 4-piston calipers. 240mm-disc rear brake with singlepiston caliper.

Convenient center stand

Height adjustable seat

ABS* (Bandit 1250SA only)

Seat height can be adjusted up or down 20mm by flipping over mounting spacers.

Sleek half-fairing, with built-in line-beam headlight and an effective windscreen.

Analog tachometer, LCD digital speedometer, LCD fuel gauge and clock, and LED indicator lamps.

Specifications		
Engine Type		4-stroke, 4-cylinder, liquid-cooled, DOHC
Engine Displacement		1255 cm³ (76.6 cu. in)
Bore x Stroke		79.0 mm x 64.0 mm
Compression Ratio		10.5 : 1
Transmission		6-speed constant mesh
Overall Length		2130 mm (83.9 in)
Overall Width		790 mm (31.1 in)
Overall Height		1235 mm (48.6 in)
Wheelbase		1485 mm (58.5 in)
Ground Clearance		135 mm (5.3 in)
Seat Height	Low / High	805 / 825 mm (31.7 / 32.5 in)
Curb mass	Bandit 1250S/SA	250 kg (551 lbs) / 254 kg (560 lbs)
Suspension	Front	Telescopic, coil spring, oil damped
	Rear	Link type, coil spring, oil damped
Brakes	Front	Disc, twin
	Rear	Disc
Tires	Front	120/70ZR17M/C (58W), tubeless
	Rear	180/55ZR17M/C (73W), tubeless
Ignition Type		Electronic ignition (Transistorized)
Fuel Tank		19.0 L (5.0 US gal)
Colors		

Specifications

Photo : Bandit 1250SA





Glass Sparkle Black (YVB)

Specifications, appearance, colors (including body color), equipment, materials and other aspects of the "SUZUKI" products shown in this catalogue are subject to change by Suzuki at any time without notice, and they may vary depending on local conditions or requirements. Some models are not available in some regions. Each model may be discontinued without notice. Please inquire at your local dealer for details of any such changes.

Always wear a helmet, eye protection and protective clothing. Read your Owner's Manual carefully.

Read your Owner's Manual carefully.
 Never ride under the influence of alcohol or c
PRINTED IN JAPAN Bandit 1250S/SA (GSF1250S/SA) Leaflet 99999-A0013-121 AUG.'11
SUZUKI MOTOR CORPORATION

300 Takatsuka-cho, Minami-ku, Hamamatsu City, JAPAN 432-8611

www.globalsuzuki.com

★ Please note that ABS is a supplemental device for brake operation, not a device for shortening stopping distance. Always remember to reduce speed sufficiently before approaching curves and corners

\$SUZUKI