

DR 200SE



Smooth, Agile In The Rough Or In The City

The DR200SE is the definition of a dual purpose motorcycle.

It delivers performance that makes it easy to ride on the street, and also you'll enjoy the dependability you need from a dirt bike. Equally at home, in the city, or in the country – the DR200SE.

DR 200SE



Solid Black (019)



Push-button electric engine starter



Front disc brake



Easy-to-read instruments

- 199cm³, 1-cylinder, SOHC engine produces lots of usable torque in spite of its conveniently compact and lightweight design.

- Suzuki Composite Electrochemical Material (SCEM)-plated cylinder for durability, lightweight and superior heat transfer.

- Rider-friendly electric engine starter for easy start.

- Digitally controlled CDI ignition system to match ignition timing throughout the engine rpm range.

- Quick-action rack-and-pinion clutch design ensures light and positive clutch operation.

- Front disc and rear drum brakes deliver reliable stopping power.

- Telescopic front forks and single shock absorber rear suspension with adjustable spring preload have sufficient wheel travels of both front and rear 205mm (8.1 in).

- Compact and sturdy high-tensile strength steel pipe frame.

- Smooth, ergonomic bodywork facilitates rider to transfer weight.

- Large front and thick rear tires with special tread pattern for good traction delivery.

- Comfortable spacious seat, low seat height and compact chassis design provide easy handling.

- 13.0-liter (3.4 US gal) fuel tank and fuel-efficient engine bring long range between refueling.

- Backward-folding rearview mirrors, gearshift and brake pedals help reduce damage on the way of obstacles.

- Large, easy-to-reach grab bar also useful for attaching luggage net.

- Low-maintenance, long-life sealed chain.

- Large bright 60/55W halogen headlight.

Specifications

Engine Type	4-stroke, 1-cylinder, air-cooled, SOHC	
Engine Displacement	199 cm ³ (12.1 cu. in)	
Bore x Stroke	66.0 mm x 58.2 mm	
Compression Ratio	9.4 : 1	
Transmission	5-speed constant mesh	
Overall Length	2150 mm (84.6 in)	
Overall Width	805 mm (31.7 in)	
Overall Height	1185 mm (46.7 in)	
Wheelbase	1405 mm (55.3 in)	
Ground Clearance	260 mm (10.2 in)	
Seat Height	810 mm (31.9 in)	
Curb Mass	126 kg (278lbs)	
Suspension	Front	Telescopic, coil spring, oil damped
	Rear	Link type, coil spring, oil damped
Brakes	Front	Disc
	Rear	Drum
Tires	Front	70/100-21M/C 44P, tube type
	Rear	100/90-18M/C 56P, tube type
Ignition Type	Electronic ignition (Transistorized)	
Fuel Tank Capacity	13.0 L (3.4 US gal)	

Colors



Solid Special White No.2 (30H)

Specifications, appearance, colors (including body color), equipment, materials and other aspects of the "SUZUKI" products shown in this catalogue are subject to change by Suzuki at any time without notice, and they may vary depending on local conditions or requirements. Some models are not available in some regions. Each model may be discontinued without notice. Please inquire at your local dealer for details of any such changes.

■ Always wear a helmet, eye protection and protective clothing. ■ Enjoy riding safely.
 ■ Read your Owner's Manual carefully. ■ Never ride under the influence of alcohol or other drugs.

PRINTED IN JAPAN DR200SE Leaflet 99999-A1311-131 APR.'12
SUZUKI MOTOR CORPORATION
 300 Takatsuka-cho, Minami-ku, Hamamatsu City, JAPAN 432-8611

www.globalsuzuki.com

